

NEW!

RapidPakRx

*Adherence Strip Packager for any Retail Pharmacy
with Universal Cartridges & Built-in Vision Inspection*

No more calibrated cassettes.



Experience the unparalleled, adherence packaging automation technology of the RapidPakRx™. The RapidPakRx runs 20 “smart” bulk-loaded universal cartridges that dispense all oral solid medications such as gel caps, half tabs, new generics, etc.—**without calibration**. Run a 30-day med cycle at the lowest possible cost. No “pill-at-a-time” loading. No more trays or remote tray filling stations. Plus, no more errors from hand filling trays.

Our unique, 3-step, integrated machine vision verification system enables one-pass workflow, unmatched accuracy, and significantly lower operating cost. No need to stock expensive inventory. There’s less inventory cost, less expiration waste, and no refills during a run. Cleaning is far less time consuming. More things get done in less time, greatly enhancing pharmacy efficiency.

RapidPakRx has the lowest daily operating costs in the industry—we use automatic, variable pouch length and our consumable pouch material costs are notably the least expensive. Thermal printing means no ink ribbons. If you’ve passed up strip packaging before—time to reconsider!



- All-in-one design, no separate vision inspection machine
- Most advanced features industrywide, made in the USA
- Unmatched speed, flexibility, and accuracy
- Runs 20 “smart” bulk-loaded, universal cartridges simultaneously—dispense all oral solid medications (including gel caps, half tabs, new generics, etc.)
- No more trays, no more remote tray filling stations
- Unique 3-step, integrated machine vision verification system—one-pass workflow, no secondary machine

- Up to 50 single or multi-med pouches/min.
- Positive displacement pouch filling
- No more expensive consumables
- Less labor
- Smallest footprint (33” wide, 18” deep, 60” high)
- Less on hand inventory required
- Intelligent software without extravagant pricing



Phone: 877.797.2332
Email: info@rxsafe.com
www.rxsafe.com

2453 Cades Way, Suite A
Vista, CA 92081

Specifications for RapidPakRx™ System

• Dimensions	W=33" L=18" H=60"
• Weight	395 lbs.
• Dispensing Capacity	20 new "smart" bulk-loaded universal cartridges (for any size pill)
• Pouch Fill Rate	Up to 50 multi-med pouches per minute
• Communications	Ethernet connection to workstation(s) & pharmacy management software
• Internal Temperature/Humidity	Same as pharmacy space
• Internal Cleanliness	Easiest cleaning in the industry
• Equipment	Packager includes: Built-in controller, power supplies, 20 "smart" bulk-loaded universal cartridges with 20 built-in vision inspection systems, consumables sensors, thermal printer
• Workstation	PC, monitor, biometric fingerprint reader, keyboard, mouse, "smart" filling station with built-in vision verification
• Verification	Unique 3-step integrated machine vision verification system, includes final pouch machine vision verification
• Software	Proprietary RxSafe software and firmware

Specifications for RxSafe Controller (built-in)

• Computer	Industrial quality with 2x256GB solid state hard drives
• Operating System	Microsoft Windows 10 Professional, 64-bit
• Database	Microsoft SQL Server
• Power	110 volt A/C, 20 amp

RapidPakRx Field Performance Data

Cost Reduction	Far less cleaning & maintenance = less down time Fastest fill rate in the industry Positive displacement multi-med pouch filling Lowest cost consumables in the industry Automatic, dynamic pouch sizing means one pouch per med pass Hi-fidelity, direct thermal printing—no print ribbon Utilizes RxSafe newly patented "smart" bulk-loaded universal cartridges No "exceptions tray" or tray filling station No "pill-at-a-time" loading Smallest footprint, easiest to use
----------------	---

Custom Pharmacy Layout Services

Workflow Optimization	Integrates RxSafe systems' automation into existing pharmacy space
-----------------------	--



Phone: 877.797.2332
Email: info@rxsafe.com
www.rxsafe.com

2453 Cades Way, Suite A
Vista, CA 92081

Revised 0- .%\$.&\$